

FAT-C4PA

16-Core Fiber Distribution Box

Application

- Designed for FTTH networks, connecting distribution and drop cables at user access points.
- IP68-rated enclosure ensures robust performance for indoor and outdoor wall or pole mounting.



Specifications

Part No.	FAT-C4PA	
Dimensions	210×112×92 mm	
Enclosure Material	PC+ABS	
Cable Entry Ports	1 Port × PG13.5 or Hardened Adapter	
Cable Exit Ports	4 Ports × Hardened Adapter	
Patching Capacity	4 SC or LC Duplex Adapters	
Splicing Capacity	4/8 Fibers (Single-core)	
Suitable Splitter	1×4 Micro PLC Splitters	
IP Rating	IP68	
Mounting	Wall / Pole Mount	



Features & Benefits

- Constructed from durable PC/ABS for superior strength and environmental resistance.
- Supports 4 hardened adapters for efficient and reliable connectivity.
- Accommodates a 1:4 micro PLC splitter for streamlined signal distribution.
- Supports up to 4 or 8 fiber splices for flexible fiber management.
- Plug-and-play design simplifies installation, reducing labor and splicing costs.
- Compact and integrated design combines cable fixation, storage, splicing, and distribution.
- IP68 rating provides exceptional protection against dust and water in harsh conditions..

Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	ı	4 Poiro
	(for Wall mount Only)	1	4 Pairs
	Pole-mounting Kit	Clamp: Ø216mm	2 PCS
	(for Pole mount Only)	Clamp. Ø2 fomm	
	Splice Sleeve	1.2/45mm	12-24 PCS/Tray
	Nylon Cable Tie	3×100mm	10 PCS

Packing List

Part No.	Carton Size	PCS/CTN	G.W.
FAT-C4PA	50×44×22 CM	20	15 KGS