

FB-T433

Compact Fiber Optic Floor Distribution Box (Splice Type)

Application

- Designed for providing full splice and perfect fiber management in building or small street cabinet environments.
- IP43 Rated, supports wall-mounted installation.






Features & Benefits

- Features a compact structure that allows for full splicing and perfect fiber management.
- The box cover uses a hinge and snap joint, making installation and uninstallation easy.
- Operating space is divided into two parts for convenient loop-through cable and pigtail splicing.
- Each of the two splice trays is equipped with a transparent plastic cover to protect the fibers.
- The splice tray features a convenient flip design for ease of access during maintenance.
- Suitable for the application of Micro PLC splitters (1x4 or 1x8) within each tray.
- Includes a nylon thread to securely attach the box door to the base.

Specifications

Part No.	FB-T433
Dimensions	150 × 108 × 36 mm
Housing Material	ABS or PC/ABS
Cable Entry / Exit Ports	1 / 1 In-line Ports × Ø13mm
Drop Cable Ports	8 Ports × Ø4mm
Patching Capacity	Not Supported
Splicing Capacity	8 Fibers
Number of Splice Tray	2 Trays
Splices per Tray	4 Fibers / Tray
Suitable Splitter	1×4 or 1×8 Micro PLC Splitter / Tray
IP Rating	IP43
Mounting	Wall Mount

Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Nylon Cable Tie	3 × 100 mm	16 PCS
	Splice Sleeve	Ø1.2 × 45 mm	4 PCS / Tray

Packing List

Part No.	PCS/CTN	G.W.	Carton Size
FB-T433	50	12 KG/CTN	60 × 34 × 25 cm