

FDB-16JD

16-Port Fiber Distribution Box

Application

- Serves as a critical termination point in FTTx networks, facilitating the connection between feeder cables and drop cables, with integrated functions for fiber splicing and distribution.
- IP65-rated to resist dust and water, suitable for both wall-mounted and pole-mounted installations in outdoor or harsh indoor environments, providing robust protection for FTTx, telecom, and CATV network infrastructure.






Features & Benefits

- Constructed from PC+ABS material with anti-UV properties, ensuring long-term performance against sunlight and environmental degradation.
- Supports 32-core splicing and 24 SC patching, meeting medium-scale network distribution needs for FTTx and telecom systems.
- Accommodates cable diameters from 8mm to 13mm, compatible with cord cables, patch cords, and drop fibers for versatile routing.
- Maintains a fiber bend radius of over 30mm to prevent signal loss and ensure optical performance integrity.
- Designed for simple access and capacity expansion, reducing downtime during upgrades or repairs.
- Compatible with wall mounting, pole mounting (via hose clamps), and optional cable storage setups, adapting to diverse site conditions.


Specifications

Part No.	FDB-16JD	
Dimensions	253×198×100 mm	
Material	PC+ABS	
Main Cable Ports	2 Mid-span ports × Ø8-13mm (for Un-cut cable)	
Branches	1 × PG13.5	
Drop Cable Ports	16 × Ø3mm	
Patching Capacity	24 SC Adapters	
Splicing Capacity	32 Fibers (Single-core)	
Splice tray	1 Tray	
Suitable Splitter	Two of 1×8 Micro PLC Splitter	
IP Rating	IP65	
Mounting	Wall / Pole Mount	


Routing







Mounting Options



Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit (for Wall mount Only)	1	4 Pairs
	Pole-mounting Kit (for Pole mount Only)	Clamp: Ø216mm	2 Pairs
	Spirally Wound Tube	L=50mm	1 PC
	Nylon Cable Tie	3×100mm	8 PCS
	Splice Sleeve	1.2/45mm	16 PCS
8	Key	1	1 PC
	Cable Storage Frame	1	(Optional)



Packing List

Part No.	Carton Size	PCS/CTN	G.W.
FDB-16JD	44×59×53CM	20	25KG