

FDB-24N3

24 Cores Fiber Distribution Box

Application

- Designed for FTTx networks, serving as a termination point for connecting drop cables to feeder cables for up to 24 users.
- IP55-rated enclosure supports reliable indoor and outdoor installations with wall or pole mounting options.








Features & Benefits


- Constructed from high-quality PC+ABS or ABS for superior strength and durability.
- Supports up to 24 fiber cores with a double-page design for easy installation and maintenance.
- Accommodates up to 4x1:8 tube splitters for efficient signal distribution.
- Features a special-shaped lock for secure and easy access with enhanced waterproof performance.
- Independent rubber sealing plug for drop cables ensures reliable water resistance.
- Fusion and termination areas are fully separated for streamlined operations.
- Compact yet spacious design optimizes fiber splicing, splitting, and storage.


Specifications

Part No.	FDB-24N3	
Dimensions	344×210×103 mm	
Enclosure Material	PC+ABS	
Cable Entry Ports	2 Mid-span ports × Ø14mm	
Branches	2 × PG16	
Cable Exit Ports	24 Drop ports × Ø2-5mm	
Patching Capacity	24 SC Adapters	
Splicing Capacity	48/96 Fibers (Single-core)	
Splice Tray	4 Trays	
Suitable Splitter	1×8 or 1×16 Micro PLC Splitters	
Material of Tray	ABS	
IP Rating	IP65	
Mounting	Wall / Pole Mount	

Dimension Diagram (mm)











Wall-mounted & Pole-mounted





Wall Mount

Pole Mount

Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit (for Wall mount Only)	1	4 Pairs
	Pole-mounting Kit (for Pole mount Only)	Clamp: Ø216mm	2 PCS
20	Metal Plate	1	2 PCS
	Nylon Cable Tie	3×100mm	10 PCS
	Splice Sleeve	1.2/45mm	12-24 PCS/Tray
	Hose Clamp	1	4 PCS
	PG Gland	PG16	2 PCS
	Key	1	1 PC
	Installation Menu	1	1 PC

Packing List

Part No.	Carton Size	PCS/CTN	G.W.
FDB-24N3 with wall -mounting kit	45×37×52CM	10	21 KG
FDB-24N3 with pole -mounting kit	57×37×47 CM	8	17 KG