

FDB-8BJ2

8-Core Fiber Optic Distribution Box

Application

- Designed for fiber optic distribution in FTTH networks, serving as a termination and splicing point for main and drop cables.
- IP55 Rated, suitable for wall-mounted and pole-mounted installations.












Features & Benefits


- Constructed from durable CPP (PP Resin) for reliable performance in varied conditions.
- Supports up to 8 SC adapters for efficient fiber connectivity.
- Accommodates a 1x8 micro PLC splitter for streamlined signal distribution.
- Features one splice tray with 12 fiber capacity for organized fiber management.
- Includes two mid-span ports (Ø14 mm) and eight drop ports (Ø2.0-4.6 mm) for flexible cable routing.
- Silicon rubber seals for cover and ports ensure robust IP55 protection.
- Supports aerial, wall, or pole mounting for versatile deployment options.


Specifications

| Part No. | FDB-8BJ2 | |
|--------------------|----------------------------|--|
| Dimensions | 219×155×82 mm | |
| Enclosure Material | CPP (PP Resin) | |
| Main Cable Ports | 2 Mid-span ports × Ø14mm | |
| Drop Cable Ports | 8 × Ø2-4.6mm | |
| Patching Capacity | 8 SC Adapters | |
| Splicing Capacity | 12 Fibers (Single-core) | |
| Splice tray | 1 Tray | |
| Suitable Splitter | 1×8 Micro PLC splitters | |
| IP Rating | IP55 | |
| Mounting | Aerial / Wall / Pole Mount | |

Dimension Drawing










Mounting Options



Standard Accessories

| Picture | Name | Size | Quantity |
|---------|--|---------------|----------|
| | Wall-mounting Kit (for Wall mount Only) | 1 | 2 Pairs |
| | Pole-mounting Kit (for Pole mount Only) | Clamp: Ø216mm | 2 Pairs |
| * | Aerial Kit (for Aerial mount Only) | 1 | 2 Pairs |
| | Nylon Cable Tie | 3×100mm | 4 PCS |
| | Splice Sleeve | 1.2/45mm | 12 PCS |
| | Installation Manual | A5 | 1 PC |

Packing List

| Part No. | Carton Size | PCS/CTN | G.W. |
|----------|-------------|---------|--------|
| FDB-8BJ2 | 47×39×33 CM | 10 | 15 KGS |