

## GJS-B330C-3P

### 3 Ports Fiber Optic Splice Closure

#### Application

- Applicable for the FTTx project and provide mechanical protection for fiber management system that includes the functions of splicing, cable fixing and passive component integration
- Rated to IP68, suitable for outdoor direct burial, aerial, wall or pole mount application.








## Features & Benefits

- Accommodates up to 48 fiber splices across 4 trays, allowing for efficient fiber management.
- Includes 3 ports (max. Ø18mm) for flexible installation configurations.
- Provides full protection against dust and water, making it suitable for outdoor and harsh conditions.
- Suitable for various installation methods, including direct burial, aerial, wall or pole mount, adapting to different network needs.

## Specifications

Part No.	GJS-B330C-3P
Dimensions (L×W×H)	330×220×110 mm
Material of Enclosure	MPP
Cable Sealing Method	Rubber Grommet
Cable Entry/Exit Ports	3
Port Diameter	Ø8-18mm
Splicing Capacity (Max)	48 Fibers (Single-core)
Number of Splice Trays (Max)	4 Trays
Material of Trays	ABS
IP Rating	IP68
Mounting	Aerial / Wall / Pole Mount / Direct Buried

## Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit (for wall mount only)	/	4 Pairs
	Pole-mounting Kit (for pole mount only)	Clamp: Ø216mm	2 PCS
	Aerial Kit (for Aerial Only)	/	2 PCS
	Nylon Cable Tie	3*100mm	3 PCS
	Splice Sleeve	1.2/45mm	12 PCS/Tray (Optional)
	Small Clamp	Ø18mm	3 PCS
	Allen Wrench	/	1 PC

## Packing List

Part No.	Carton Size	PCS/CTN	G.W.
GJS-B330C-3P	67x35x63CM	15	29KGS