

# GJS-H1102

## 1-IN 1-OUT Fiber Optic Splice Closure

### Application

- Ideal for aerial, manhole, direct-buried, and wall-mounted installations to protect fiber splices in FTTH and telecom networks.
- Suits drop cable connections requiring compact and high-protection solutions.





### Specifications

Part No.	GJS-H1102
Dimensions (L×W×H)	178×117×22.5 mm (7.01×4.61×0.89 in)
Material of Enclosure	ASA
Color	White
Cable Sealing Method	Rubber Grommet
Cable Entry/Exit Ports	1 / 1 (In-line)
Cable Ports Diameter	Ø7.5mm
Splicing Capacity (Max)	2/4 Fibers (Single-core)
IP Rating	IP68
Mounting	Aerial / Wall Mount / Direct-Buried

## Features & Benefits

- Compact design (178×117×22.5 mm) for space-saving installations in tight environments.
- ASA material housing with excellent anti-aging and UV resistance for long-term outdoor use.
- IP68-rated rubber grommet sealing system, reusable for multiple installations.
- 2 cable ports (max.  $\varnothing 7.5$  mm) supporting 2–4 single-core fiber splices.
- Wall or aerial mounting compatibility with optional kits.

## Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Hook	/	2 Pairs
	Splice sleeve	$\varnothing 1.2 \times 45\text{mm}$	2/4 PCS
	Electrical Tape	/	1 Roll
	Rubber Cement	100mm	1 PC
	Hex Key	M6	2 PCS/CTN

## Packing List

Part No.	Carton Size	PCS/CTN	G.W.
GJS-H1102	55×41×27 CM	64	20 KG
GJS-H1102	55×41×27 CM	90	23 KG