

GJS-H3350C-6T

3-IN 3-OUT In-line Fiber Optic Splice Closure


Application

- The GJS-H3350C-6T In-line Fiber Optic Splice Closure is designed for outdoor fiber optic networks, supporting secure splicing and distribution of up to 288 fibers.
- IP68-rated for reliable performance in direct-buried and aerial installations, ensuring protection in harsh environmental conditions.











Key Features

- **High-Capacity Design:** Accommodates 6 splice trays with 24–48 fusions per tray, totaling up to 288 fibers for large-scale network deployments.
- **Versatile Port Configuration:** 3 inlets + 3 outlets (in-line) with mixed diameters (2ר16 mm + 4ר23 mm) to support diverse cable sizes.
- **Dual Installation Options:** Optimized for both aerial (with optional hanging kit) and direct-buried setups, adapting to varied project needs.
- **Durable Construction:** MPP housing (PC optional) with excellent resistance to UV, corrosion, and mechanical stress, ensuring long-term reliability.
- **Secure Sealing:** Silicone seals for cable ports and mechanical seals for the closure body achieve IP68 protection, preventing water and dust ingress.
- **Efficient Maintenance:** Transparent splice tray covers enable easy fiber inspection, while reusable components reduce maintenance costs.

Specifications

Part No.	GJS-H3350C-6T		
Dimensions (L×W×H)	495×175×130 mm (19.49×6.89×5.12 in)		
Material of Enclosure	PC or PC+ABS		
Cable Sealing Method	Rubber Grommet		
Cable Entry/Exit Ports	3 / 3 (In-line)		
Port Diameter	2ר16 mm & 4ר23 mm		
Splicing Capacity (Max)	288 Fibers (Single-core)		
Number of Splice Trays (Max)	6 Trays		
Material of Trays	ABS		
Inflating Valve	Not Supported		
Grounding Device	Not Supported		
IP Rating	IP68		
Mounting	Aerial / Direct-buried		

Mounting Options

• **Aerial**: After installing the hooks on the Hex Screws at both ends on the same side of the product, hang the product on the steel cable and tighten the screws at the hooks.





Accessories

Picture	Name	Size	Quantity
*	Aerial Kit (for Aerial Only)	1	2 Pairs
	Rubber Block (Small)	Ø16mm	2 PCS
	Rubber Block (Big)	Ø23mm	4 PCS
	Nylon Cable Tie	3*100mm	10 PCS
	Splice Sleeve	1.2/45mm	144 -288 PCS
	Electrical Insulation Tape	1	1 Roll
	Sealing Compound	I	1 Roll
	Hex Wrench (L Type)	M5	1 PC
	Hex Wrench (L Type)	M6	1 PC
4	<u>Nut</u> Wrench	/	1 PC

Packing List

Part No.	Carton Size	PCS/CTN	G.W.
GJS-H3350C-6T	53×50×30 CM	4	19 KG