

## GP-T404-12F

### 12-Core Fiber Optic Floor Terminal Box

#### Application

- Tailored for FTTH applications in multi-dwelling units, installed on each floor as a transition point between riser and horizontal cables.
- Provides storage for excess fiber lengths, terminated fibers, and serves as a dedicated splice location.






## Features & Benefits

- Removable cover secured with a screw lock for reliable protection and access.
- Internal space divided into two sections to accommodate straight-through or loop-through cable configurations.
- Splice tray with flip design, allowing a 90-degree opening for simplified maintenance.
- Supports three main cable entries (Ø15 mm) and twelve drop cable ports (Ø3 mm).
- Splice capacity of 12 fibers for organized fiber handling in compact spaces.
- Compact form factor optimizes installation in floor environments.

## Specifications

Part No.	GP-T404-12F
Dimensions	123×183×37 mm
Enclosure Material	ABS or PC/ASB
Main Cable Port	3 × Ø15mm
Drop Cable Port	12 × Ø3mm
Patching Capacity	Not Supported
Splicing Capacity	12 Fibers
Splice tray	1 Tray
IP Rating	IP54
Mounting	Wall Mount

## Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Nylon Cable Tie	3×100mm	12 PCS
	Splice Sleeve	1.2/45mm	12 PCS
	Installation Manual	/	1 PC

## Packing List

Part No.	Carton Size	PCS/CTN	G.W.
GP-T404-12F	55×41×25 CM	40	13 KGS