

GP-T9548

2-Core Inline Fiber Wall Outlet

Application

- The Fiber Wall Outlet is a compact terminal designed for protecting fiber optic splices in FTTH drop cable installations on walls or indoors.
- It features an IP20 rating and supports wall-mounted applications.





Features & Benefits

- The wall outlet uses mechanical sealing technology to ensure reliable IP20 dustproof protection in indoor environments.
- It provides 2 inline cable entry ports and 2 exit ports specifically designed for 3×2mm flat drop cables.
- The ultra-compact body measures only 95×48×11.5mm, making it ideal for space-constrained FTTH wall installations.
- Easy re-entry design allows quick maintenance without cutting cables or replacing seals.
- Integrated splice protection sleeve holder securely organizes up to 2 single fiber splices.
- High-impact, UV-resistant polypropylene material operates reliably from -40°C to +65°C.
- Tool-free installation and lightweight design reduce deployment time in FTTH networks.

Specifications

Part No.	GP-T9548
Dimensions	95 × 48 × 11.5 mm
Material	ABS (UL94 V0 Optional)
Color	White (Customizable)
Mounting	Wall Mount
IP Rating	IP20
Cable Entries	2 / 2 In-line Ports
Supported Cable	3×2 mm Flat Drop Cable
Storage of Fibers	G.657 Fiber
Adapter Ports	Not Supported
Adapter Type	Not Supported
Splicing Capacity	2 Fibers
Splicing Method	Fusion Splice
Compatible Fiber	G.657A1/A2/B3
Operating Temperature	-40°C to +70°C

Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Splice Sleeve	Ø1.2 × 45 mm	2 PCS

Ordering Information

Part No.	Description
GP-T9548	Empty box (no adapters, no pigtails)

- ◆ Other configurations are available upon request. Customization supported.

Packing List

Part No.	PCS/CTN	G.W. / CTN	Carton Size
GP-T9548	800	18 KGS	46.5 × 31 × 40.5 CM

- ◆ Default packaging: one unit per transparent PE bag (cost-effective, most popular).
- ◆ Individual inner box is available as customized packaging. Extra charge applies.